



THE PRODUCT

Presto process inks are very fast setting and quick drying on papers and boards. They do not skin in the tin or in the duct overnight.

SPECIAL FEATURES

We believe that *Presto* process inks are the fastest setting and quickest drying available at the present time. They were produced as a result of the demand for inks that could be backed up rapidly on very short run work, without sacrificing brightness and gloss. Although originally intended for short run work, they are now being adopted by printers for long runs as well, due to their excellent press stability. They require only the minimum of spray powder, on many jobs they require no spray at all. To gain confidence with this feature, we suggest you run 50 sheets at the bottom of the stack, WITHOUT SPRAY POWDER, and see for yourself how they resist clinging and set-off, even when running full stacks. They achieve a high degree of scuff resistance a few hours after printing, and give excellent rub resistance on matt coated papers and boards. They are suitable for running on single, two and four colour machines, and all damping systems including alcohol. They have a high response to infra red drying. They are packed in conventional tins, with easy-to-open, easy-to-replace, lids. They do not skin for several days once open. Without skin there is no waste of ink, or time, and they eliminate hickies and spots, so often experienced once a can is opened.

MACHINE INFORMATION

<input checked="" type="checkbox"/>	Overnight in duct	
<input checked="" type="checkbox"/>	Overnight on rollers	
<input checked="" type="checkbox"/>	Alcohol damping	
<input checked="" type="checkbox"/>	Integrated damping	
<input checked="" type="checkbox"/>	Single colour printing	
<input checked="" type="checkbox"/>	Letterpress/Litho	
	Spray powder	KEEP TO MINIMUM
	Reducer	GELO or RELEASE AGENT

PRINTING INFORMATION

<input checked="" type="checkbox"/>	Board coated/uncoated	
<input checked="" type="checkbox"/>	Paper coated/uncoated	
<input checked="" type="checkbox"/>	Plastics/Foil/Polyart	OK ON POLYART 2

AFTER PRINTING INFORMATION

<input checked="" type="checkbox"/>	U/V Lacquer	TEST FIRST
<input checked="" type="checkbox"/>	Lamination	TEST FIRST
<input checked="" type="checkbox"/>	Rub resistant	
<input checked="" type="checkbox"/>	Gloss	SEE OVERLEAF
<input checked="" type="checkbox"/>	Fast to light	SEE OVERLEAF
<input checked="" type="checkbox"/>	Food quality	
<input checked="" type="checkbox"/>	Taint/Odour	TEST FIRST

FURTHER INFORMATION OVERLEAF